## PRINTER RUSH

(PTO ASSISTANCE)

Application: $10/8/7$	531 Examiner:	Wilson GAU:	28/5
From:	P Location:	(DC) FMF FDC Date:	2/22/06
Tracking #: epm 10/817,531 Week Date: 12/12/05			
DOC CO		MISCELLANEOUS  Continuing Data Foreign Priority Document Legibility Fees Other	
[RUSH] MESSAGE: Page + paragraph [0017]  Please provide missing Fig.7" data.			
[XRUSH] RESPONSE:			
INITIALS: DS			

NOTE: This form will be included as part of the official USPTO record, with the Response document coded as XRUSH. **REV 10/04** 

[0012] FIG. 2 illustrates a perspective view of one method of fabricating an organic electronic package in accordance with the present techniques;

[0013] FIG. 3 illustrates a cross-sectional view of another embodiment of an organic electronic package in accordance with the present techniques;

[0014] FIG. 4 illustrates a cross-sectional view of yet another embodiment of an organic electronic package in accordance with the present techniques;

[0015] FIG. 5 illustrates a cross-sectional view of an exemplary composite substrate that may be implemented in conjunction with the present techniques;

[0016] FIG. 6 illustrates a cross-sectional view of another exemplary composite substrate that may be implemented in conjunction with the present techniques; and

FIG. ')

[0017]  $\Lambda$  illustrates a cross-sectional view of still another embodiment of an organic electronic package in accordance with the present techniques.

## **DETAILED DESCRIPTION**

[0018] Fig. 1 illustrates an organic package having a flexible substrate 12. The flexible substrate 12 generally comprises a substantially transparent film. As used herein, "substantially transparent" refers to a material allowing a total transmission of at least about 50%, preferably at least about 80%, of visible light (i.e., having a wave length in the range from about 400nm to about 700nm). The flexible substrate 12 is generally thin, having a thickness in the range of approximately 0.25-50.0 mils, and preferably in the range of approximately 0.5-10.0 mils. The term "flexible" generally means being capable of being bent into a shape having a radius of curvature of less than approximately 100 cm.

[0019] The flexible substrate 12 may be dispensed from a roll, for example. Advantageously, implementing a roll of transparent film for the flexible substrate 12 enables the use of high-volume, low cost, reel-to-reel processing and fabrication of the organic package 10. The roll of transparent film may have a width of 1 foot, for example, on which a number of organic packages may be fabricated and excised. The